



## MODEL RANGE

Vehicle loading conveyors are used for the rapid handling of mixed cargo such as packages, boxes and loose goods like tyres and furniture.

### Telescopic Belt Booms

Fixed boom conveyors are so called because they are installed in one position, ideal for loading docks.

### Gravity Fixed Roller Telescopic

Fixed boom conveyors with gravity rollers, installed in one position, ideal for loading vehicles.

### Mobile Belt Booms

Mobile belt booms and van loaders have a subframe with wheels that enables the conveyor to be moved easily as required.

### TELESCOPIC BELT BOOMS



	Extending Sections	Length of Base (mm)	Max Extension (mm)	Belt/Roller Width (mm)
TL2-8-12-600	2	8000	12000	600/800
TL2-5-7-600	2	5000	7000	600/800
TL3-6-12-600	3	6000	12000	600/800
TL3-7-15-600	3	7500	15000	600/800
TL4-5-12-600	4	5000	12000	600/800
TL4-7-16-600	4	7000	16000	600/800

### GRAVITY FIXED ROLLER TELESCOPIC



RL2-5-7-600	2	5000	7000	600/800/1000
RL2-6-9-600	2	6000	9000	600/800/1000
RL3-6-13-600	3	6000	13000	600/800/1000

### MOBILE BELT BOOMS



	Extending Sections	Outreach (mm)	Belt Width (mm)
MVL-6	1	6000	600
MVL-9	2	9000	600
MVL-10	1	10000	600
MVL-12	2	12000	600